

Acrylic Block Filler

Application Note

Significant Issue:

Acrylic block filler formulations incorporate Interfibe cellulose fibers to provide trowel resistance for high build, reduced weight and sag resistance.

Customer Objectives:

While maintaining product consistency, Interfibe fibers effectively replace other reology modifiers at a significant savings to the customer.

Interfibe Solution:

Interfibe 5FT will provide trowelability and sprayability at a three to five percent loading.

interfibe[™]

*For further information, call
your local distributor or
Interfibe Corporation.*

Phone: (800) 262-3771

Fax: (216) 248-2132

Acrylic Block Filler

Application Note

PVA LATEX MASONARY BLOCK FILLER USING INTERFIBE 5FT

Raw Material	Lbs.
Water	185.00
KTPP	2.00
Tamol 731	6.00
Triton M-101	2.00
Minex 2	375.00
Calcium Carbonate (20 micron)	150.00
Ethlene Glycol	18.60
Natrosol 250 HBR	1.00
<hr/> <i>High Speed Dispersion for 10 Minutes</i> <hr/>	
Interfibe 5FT	24.49
Attapulgate Clay	15.00
Texanol	8.00
Coasan PMA-60	.80
<hr/> <i>High Speed Dispersion for 5 Minutes</i> <hr/>	
UCAR 367	252.00
Defoamer	1.00
TOTAL LBS.	1,040.89
TOTAL GALLONS	92.69

Weight, lbs./gal.	11.23
Viscosity	120 KU No Drip
pH	5.5
P.V.C.	63.42%
Solids (wt.)	52.50%
Solids (vol.)	45.09%

The data included represent typical product characteristics. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed to in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

interfibe

*For further information, contact
your local distributor or
Interfibe Corporation.*

**Phone: (800) 262-3771
Fax: (216) 248-2132**