

Acrylic Textured Paint

Application Note

Significant Issue:

Interfibe 5FT will provide various degrees of texture in latex wall and ceiling paints. As an alternative to other textures, the internal fibrous network has a woven surface appearance.

Customer Objectives:

The surface texture of a specific formulation can be modified with different lengths of cellulose fibers. The Interfibe grade must provide desired texture and viscosity control and be compatible with customer application equipment.

Interfibe Solution:

Interfibe 5FT is for trowel, brush, roller or fine nozzle spray Application of textured coatings.

interfibeTM

*For further information, call
your local distributor or
Interfibe Corporation.*

**Phone: (800) 262-3771
Fax: (216) 248-2132**

Acrylic Textured Paint

Application Note

INTERIOR ACRYLIC TEXTURE WHITE USING INTERFIBE 5FT

Raw Materials	Lbs.
Water	200.00
Ethylene Glycol	18.56
Natrasol 250 HBR	1.00
Cosan PMA-60	.20
KTPP	2.00
Tamol 731	4.00
Defoamer	1.00
TiO ₂	50.00
Air Floated Clay 325 Mesh	150.00
Calcium Carbonate	150.00
Interfibe 5FT	21.75

High speed dispersion for 10 minutes

Add:

Attapulgite Clay	15.00
------------------	-------

Mix until smooth

Add at Slow Speed:

Water	166.60
Triton- M-101	2.00
Texanol	8.00
Natrosol 250 HBR	2.00
UCAR 367	225.00
Defoamer	1.00
TOTAL	1,018.11
TOTAL GALLONS	93.55

Weight, lbs./gal.	10.88
Viscosity	105 KU No Drip
PpH	7.8
P.V.C.	60.68%
Solids (wt.)	50.58%
Solids (vol.)	34.92%

The data included represent typical product characteristics. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed to in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

interfi

*For further information,
your local distributor or
Interfibe Corporation.*

**Phone: (800) 262-37
Fax: (216) 248-2132**