



# ROAD-CEL<sup>®</sup> Specification Sheet

Product Description	Modified cellulose fibers	METHOD
Alpine Sieve Analysis *	70.0 ± 10.0% thru 100 mesh	Interfibe 91-01
Fiber Length:	6 mm maximum	
Oil Absorption *	5.0 ± 1.0 times its own weight	Interfibe 91-02
Moisture *	<5%	Interfibe 91-03
Ash *	18.0 ± 5.0%	Interfibe 91-04
* monitored during production		
Bag Description	3 mil low- density polyethylene (coated inside for easy material discharge) 28" x 18" x 10" 44lbs/bag	
Pallet Description	4 way entry pallet : Aspen 48" x 40" Top Frame : Aspen 54" x 40" 25 bags/skid  Skid Dimensions : 58" x 48" x 52" Shipping weight : 1100 net 1150 gross	} 50 lbs

### ***Interfibe***: A TRADEMARK OF INTERFIBE CORPORATION

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our, whether used alone or in combination with other products.

---

#### INTERFIBE CORPORATION

PLANT: 1615 Vanderbilt Road  
Portage, MI 49024  
PH: 269-323-8366 FX: 269-323-1466  
ORDERS: 800-775-5524

SALES: 30285 Bruce Industrial Pkwy.  
Solon, OH 44139  
PH: 440-248-2266 FX: 440-248-2132  
Toll Free: 800-262-3771

[www.interfibe.com](http://www.interfibe.com)